

PROPOSE HOUSE ADDITION

PRESENT HOUSE - The existing house is of timber construction with weatherboard cladding, metal roofing tiles and aluminium window joinery.

THE PROJECT - To build a two storey addition at the north end of the house to accommodate a bedroom & ensuite to the first floor with an office and bedroom to the lower floor. This involves minor changes to the adjoining bedroom walls to incorporate an access corridor and a minor extension of the roof where it joins the new building.

- Check all dimensions on site before fabrication and construction.
- Check bearing capacity of ground before installing foundations.
- All construction to be in accordance with NZS 3604, Local Authority requirements and best trade practices & Engineers structural details & calcs.
- All materials, details, profiles and finishes to match ex. house to owners approval.
- All electrical & ensuite fixtures & fittings to be selected or approved by the owner.
- Plumbing & Drainage - Locate Hot & Cold water supply as agreed by owner, run drains from ensuite via the vertical duct and under ground floor to connect with existing drains.
- Rainwater - Rainwater downpipes to connect to new soakhole.
- Floors - G.F. 20mm particle bd on 150x50 joists @ 400 c/c on 150x100 bearers @ max. 2000 c/c on 150 SED Piles. See Structural Engineers calculations (Diaphragm matching to 3604).
- F.F. 20mm particle bd on 200x50 joists @ 400 c/c - Attic floor 20mm particle bd on 250x50 bottom chord of trusses and 250x50 intermediate beams.
- NOTE - All timber to ensuite floor to be H3 treated.
- Walls - External - Weatherboarding to match existing boarding & details on building paper on studwalls. Internal - 10mm Gipsboard generally with Gib Aqualine to ensuite.
- Insulation - to walls and roof to be min. R1.8 fibreglass batts (walls) and R2.2 fibreglass quilt (roof) with foil under ground floor & soundbatts where shown.
- Roof - Balfour 'Trimline' Coloursteel 500 roofing with 125x140 Fascia Gutter with Ridge, Barge & flashings to match colour chosen by owner.
- Windows - new door & window joinery selected by owner.
- NOTE: All glazing to be 5mm thick other than that marked DG (double glaze) and that in the Attic.

Revision 1 - Soakhole
Revision 2 - 150 SED Piles.

DRG NO 1 of 5


G.I. MARDON DIP. ARCH.
OCT 006.

PROPOSED HOUSE ADDITIONS

FOR JONATHAN & KAY SCOTT


246 MYSTERY CREEK ROAD · RDI · OHAUPO

SITE PLAN 1-1500




RESIDENTIAL SOAKHOLE 1-20
To take stormwater from house addition
roof of 43 M².







SOUTH 1-100




EAST 1-100




NORTH 1-100



WEST 1-100



GROUND FLOOR PLAN 1-100



FIRST FLOOR PLAN 1-100

LEGEND:

- ===== EXISTING WALLS
- WALLS FOR REMOVAL
- ===== NEW WALLS

LINTELS:


- 'A' 125 X 100
- 'B' 150 X 100
- 'C' 250 X 100

DRAINAGE:


- SOIL DRAINS
- STORMWATER DRAIN.




ELEVATION



SECTION A-A



SECTION B-B



SHOWER Plans, Sections, Elevation, 1-50

NOTE: Refer to James Hardie Building Products 'Hardiglaze' Technical Information for details of tiling complying with the New Zealand Building Code.

PART. EX. FLOOR PLAN

PROPOSED HOUSE ADDITIONS

FOR JONATHAN & KAY SCOTT


246 MYSTERY CREEK ROAD · RDI · OHAUPO

Revision 1 - Drainage



DRG NO 2 of 5

G.I. MARDON DIP. ARCH.


OCT 006.




GROUND FLOOR PLAN 1-100
& SUB FLOOR STRUCTURE



ROOF PLAN 1-100



SECTION A-A 1-50




6KN PILE FIXING.
6KN Connection to each pile.

PROPOSED HOUSE ADDITIONS
FOR JONATHAN & KAY SCOTT
246 MYSTERY CREEK ROAD • RDI • OHAUPO


Revision 1 - 150 SED Piles.

DRG NO 3 of 5.
G.I. MARDON DIP ARCH
OCT 006




M.S. Railings from
20 x 6mm flat bars &
12 φ M.S. Rods welded
all to be fixed with C/screws.

DETAIL 'J' 1-10




DETAIL 'K' 1-10




FLASHING CONNECTION
Between new addition
and existing roofs.

new wall
Fibreglass insulation
10mm Gypsum.

DETAIL 'F' 1-10




DETAIL 'I' 1-10




PLAN THRO' BALUSTRADE AT 'L' 1-10


DETAIL 'G' 1-10




DETAIL 'H' 1-10




DETAIL 'A' 1-20



DETAIL 'B' 1-20




DETAIL 'C' 1-20



DETAIL 'D' 1-20



DETAIL 'E' 1-20



PROPOSED HOUSE ADDITIONS

Revision 1 - M.S. rod spacing.
Revision 2 - 150 SED Piles.
DRG No 4 of 5
G.I. MARDON DIP. ARCH.
OCT 006.

BRACING PLANS



WEATHERTIGHTNESS RISK ASSESSMENT

House Addition - The addition has a low risk envelope complexity of similar construction to the existing building - horizontal weatherboarding on building paper on timber studwork walls with longrun corrugated roofing at a 45° pitch and a 450 mm to 600 mm eaves overhang.

ALL WALLS	RISK SEVERITY LOW RISK					Subtotals for each risk factor
Risk factor	Low	Medium	High	Very high		
Wind zone	0	0	1	2		
Number of storeys	0	1	2	4		2
Roof/wall intersection design	0	1	3	5		
Eaves width	0	1	2	5		2
Envelope complexity	0	1	3	6		
Deck design	0	2	4	6		
Total risk score:						4

PROPOSED HOUSE ADDITIONS
FOR JONATHAN & KAY SCOTT
246 MYSTERY CREEK ROAD · RDI · OHAUPO

R1 - See Struct Engineers
 Sub-Floor Spec. & Calculations.

DRG NO 5 of 5

G.I. MARDON DIP. ARCH.
 OCT 006.

**PILING
DRIVEN TIMBER PILES**

**SCOTT RESIDENCE
246 MYSTERY CREEK ROAD
RD 5, OHAUPO**

1. MATERIALS

The pile shall be naturally round with a minimum tip diameter of 150mm at the small end; and a taper of 25mm in 3.5m. The piles shall be tanalised to H.5.B for at least 3 weeks prior to usage. A timber helmet shall be used to minimize damage to the tip of the pile. Ends cut after treatment shall not be placed in the ground unless re-pressure treated.

2. PILE DRIVING

The position of each pile shall be accurately fixed on ground. The piles shall be firmly guyed to maintain their correct location and shall be checked regularly. At the end of driving, no pile shall be more than 50mm from their correct position.

3. LIMITATIONS ON DRIVING PILES

The contractor shall allow in his rates for difficulty in driving to meet the required set, and is advised to drive 2 / 3.6 m test piles before ordering the piles.

4. DRIVING MONKEY

Driving shall be carried out using a 500kg monkey. The monkey shall be so designed that the efficiency blow is not impaired. The plant shall be so designed that the monkey falls freely under its own weight and is vertical to the pile. The drop of the monkey shall be maintained at 1.2m.

5. DRIVING AND PENETRATION

Each pile shall be driven until the following conditions are reached:

- a) The piles shall be driven to a minimum of 2.0m
- b) The number of blows required with 1.2m drop over the last 300mm of penetration shall be not less than 8.
- c) The penetration produced by the last blow shall be less than 35mm.

6. INSPECTION AND COMPLETION OF PILES

The contractor will provide all assistance to the engineer/inspector to adequately inspect the pile and shall provide detail logs of the penetration achieved. The engineer/inspector will be the sole judge as to when driving shall cease. At the conclusion of driving, the piles shall be sawn off at the required height. The cut surface shall be treated with a concentrated solution of copper naphthenate.

Along with the final results, the contractor shall provide a completed PS 3 Form to the Engineer, before any further work is undertaken.